
FP-3000ts

Flat-Panel Display for Honeywell Classic Universal Stations

*A low-maintenance, long life upgrade
for your Universal Stations*

A high quality replacement display

This LED-Backlit flat-panel display was designed as a direct replacement for the CRT-based monitors used in Honeywell's Universal Station with EPDG video, and in GUS stations in classic furniture. The display may be installed either bezel-mounted, to bring it closer to the operator. Connect the power cable, video cable, and touch screen cable to the new display and you're up and running.

Integrated flat touch screen

The FP-3000 comes with a flat infrared touch screen mounted to the front of the display. This touch screen is mounted a few millimeters from the display surface, and eliminates "false picks" sometimes seen with the old touch screen because of its distance from the screen. 9-pin Serial or USB connection options.

Bright image, durable screen

The LCD plastic surface is protected by a glass antiglare layer attached to the front of the display. This durable surface protects the LCD from the wear scratches that any plastic surface eventually suffers after repeated cleaning (or touching with fingers, pencils, or sharp objects). The antiglare treatment of the glass combined with the inherent low-glare characteristics of a flat display results in a high-contrast display that is easy on the eyes.

Ordering info:

The bezel-mount option comes with bezel, please specify upper or lower tier when ordering.



Low maintenance

The solid-state design of the flat-panel LED-Backlit display provides inherent reliability, low power consumption, and low maintenance. This LCD technology is expected to last twice as long as CRT-based monitors. Setup adjustments are accomplished using an intuitive button and joystick interface to control the on-screen menu. Once initial adjustments have been made, the on-screen control feature may be disconnected, preventing unauthorized adjustments to the display.

Specifications

Viewable Area: 19" diagonal (14.81" x 11.85")

Viewing Angle: 170° horizontal, 170° vertical

Power Consumption: 30 watts, 110VAC/240VAC

Display modes supported: VGA 640x480 through VESA 1280x1024, includes EPDG scan frequency. 15-pin connector, 9-pin adapter available.

Brightness: 300 cd/m²

Operating Environment: Temperature 0-50°C, Relative Humidity < 90% at < 40°C

Weight: 8.79 kg, (17.4 lbs)



WESTERN PROCESS COMPUTERS, INC.
2033 W. NORTH LANE, SUITE 14
PHOENIX, AZ 85021

Phone: 602-997-7245
Fax: 602-997-7248
info@westernprocess.com
www.westernprocess.com